

UPT1000 Full Touch

Unattended Terminal Series

- Secure and high performance MCU
- Secure Linux operating system
- 3.5" color display with touch screen
- PCI PTS 5.x, EMV L1 and EMV L2 certified
- Built-in magnetic stripe, contact and contactless readers
- Supports ISO 14443 Type A, B, ISO 18092 NFC and Sony FeliCa
- Supports RS-232, USB, Ethernet and GPRS/3G
- Supports MDB/EXE interface

Castles Technology's newly designed UPT1000F device offers multifunctional capabilities for your unattended payment needs such as vending, ticketing, multimedia kiosks, public transportation, laundromats and any other self service solutions. The UPT1000F is based on a secure Linux platform and has integrated PIN pad, magnetic stripe, chip and contactless card reader functions.

The UPT1000F is a perfect, durable and cost-effective device for any unattended business needs.



FEATURES & BENEFITS



Unprecedented Security and Certifications

- PCI PTS 5.x
- EMV Contact/ Contactless Lv1
- EMV Contact Lv2
- Contactless Scheme Certifications (Paypass, Paywave, ExpressPay, D-PAS, J-Speedy, QPBOC...)



Incredibly Adaptable

- Optional Touch Availability
- Accepts all payment types
- Flexible to integrate business applications



Exceptional Performance

- High Security Processor
- Designed and tested to perform under extreme conditions
- Allows Linux open architecture OS

UPT1000F

Unattended Payment Terminal Series

SPECIFICATIONS

		UPT1000F	
Processor		32-bit Secure Microprocessor running powerful Linux based OS	
Memory	Flash/RAM	256MB/128MB	
Display		3.5" 320 x 480 Pixels Color TFT LCD	
Touch Screen		Yes	
Card Reader	Magnetic Stripe	ISO 7810, 7811, 7813 Triple Track, Bi-Directional	
Card Reader	Contact Card	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
		SAM Card	2 (Up to 4)
Card Reader	Contactless (Optional)	ISO 14443 Type A, B ISO 18092 NFC Mifare and Sony FeliCa Working Frequency 13.56MHz	
Card Reader	Dual SIM	Yes	
Communications Interface Options	Wire	RS232*3 USB OTG*1 USB Host*2	
	Wireless	2G/3G/4G Bluetooth iBeacon Ethernet	
Indicators	LED - Contactless	No	
	Speaker	Yes	
Keypad	Standard Keys	Virtual Keypad (Support PIN on touch)	
Software		SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library	
Crypto		TRNG DES T'DES AES RSA MK/SK DUKPT T'DES DUKPT	
Power Supply	Power Adaptor	9V to 34V (MDB series: 9V~48V)@1.5A~0.5A	
Dimensions (L x M x H)	Terminal	106 x 85 x 62 (mm)	
Weight		335 g	
Environment	Operating Temperature	-20°C to 65°C	
	Storage Temperature	-35°C to 65°C	
	Operating Humidity	5% to 90% non-condensing	
	Storage Humidity	5% to 95% non-condensing	
	IP Ingress Protection	IP 54	
	IK Shock Protection	IK 08	
Certifications		PCI PTS 5.x EMV L1/L2 payWave PayPass ExpressPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM PBOC L1/L2	